


Bulk Bag Loader

- A three-layered filling head featuring a stainless steel core fully encased in Seeflex ether-based urethane.
- Includes external air fitting that plugs into an 8mm pneumatic air line to inflate super strong & flexible outer layer.
- Top of loader simply snaps into a BFM® fitting spigot and features a fully encapsulated stainless steel ring to support lower end.
- Inflates in seconds and seals tight on the neck of bulk bag, eliminating product leaks.
- Much safer for workers hands as there are no pinch points.
- Can be used on bulk bags with or without plastic liners.
- **NB:** Pneumatic air-line is recommended to be set to a maximum of 6psi.



Pneumatic air inlet fitting connects to an air-line to inflate outer layer of Seeflex.



NOTE: If using in Atex Dust Zones, the up-line pipework and pneumatic air-line inlet fitting should be earthed.

Physical Properties

Surface Finish	Gloss/Gloss
Hardness (Shore A)	90
Inner Wall Thickness (+/- 10%)	0.9 mm / 1/32 inch
Tensile Strength (MPa)	40
Operating Temp Range	-25 to 110°C -13 to 230°F
Ultimate Elongation (%)	593
Tear Strength – Die C (N)	67
Surface Resistivity (Ohms)*	10 ¹⁰
Air Permeability	0

Available Sizes:	Diameter (mm):	Expands To Fit Bag Neck Sizes (mm):
<i>(standard length for all diameters is 350mm)</i>	Ø250	Ø270 - Ø340
	Ø300	Ø320 - Ø395
	Ø350	Ø370 - Ø460
	Ø400	Ø420 - Ø540
	Ø450	Ø470 - Ø590

The Seeflex material complies with the following regulations:

FDA CFR 177.1680 and 177.2600
(EC) 1935/2004, 2023–2006, 10/2011 USDA and 3A (20-).

* Tested to ASTM D-257